


PUSH-LOCK CONCRETE ANCHOR BOLT			
CABLE DIA.	PART NO.	CONCRETE ANCHOR - CARBON STEEL	CONCRETE ANCHOR - STAINLESS STEEL
1/8"	PL-AB4	RM-38	SRM-38
3/16"	PL-AB6		

**USE WITH "RED HEAD" BRAND CONCRETE ANCHOR*

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS, AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
3. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.

THE CABLE CONNECTION
 52 HEPPNER DR.
 CARSON CITY, NV 89706
 TOLL FREE: 1-800-851-2961
 PHONE: (775) 885-1443
 FAX: (775) 885-2734
 www.ultra-tec.com

MATERIAL:	316 SS	
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THE CABLE CONNECTION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THE CABLE CONNECTION IS PROHIBITED.		
PUSH-LOCK CONCRETE ANCHOR BOLT CABLE RAILING HARDWARE		SIZE DWG. NO. A SPEC SHEET REV.
DO NOT SCALE DRAWING		